

## Record of Annual Inspection

The inspector of this vehicle meets the qualification requirements contracted in D.O.T. rule 49 CFR section 396.19

102	33 Governor L	ane Blvd
P.O.	Box 433 Willia	amsport, MD 21795-0733 Inspection Location: Creensborg V.C.
P-(	(800) 635-6733	insport, MD 21795-0733
F-1	301) 223-7674	
. ,	301) 223-7674	Unit #: //a < / 1
		MFG/Year Co Serial #: 16000
OK	DEFECT N/A	
1,000,000,000	F3	1 hispection: 8-17-20
1	0 0	(Wonth / Day / Year)
		Registration valid installed in Registration Holder.
[}	0 0	Charles To a Company of the Company
H		Conspiculty Tape sides, rear ICC Assembly and rear doors (top & bottom).
47	[]	
17-		All Marker, Clearance, Stop/Turn, Flashers and License Plate Lights are operational. All Electric
B	0 0	Harnesses are secured properly. Seven way plug properly secured.  All Front and side panels are from the secured secured.
		The state of the s
4	n n	Rails are free of damage, properly fastened to cross members, posts and panels.  ICC assembly is properly secured, step is secured and to cross members.
LJ	[] []	ICC assorbit.
		The wastifully it proposition and panels.
[]_	<b>C</b> 3	ICC assembly is properly secured, step is secure and functional and has reflective tape installed.  Taillights are functioning properly; rear doors close and lock properly and have reflective tape installed.  Air Ride Suspension Spring Day of Spring Day.
13	0 0	top and bottom. Mud flaps and brackets are installed and secure.
		Air Ride Suspension Spring Ride Suspension Springs, Rebound bolts, U-Rolte Suspension
		Springs, Rebound bolts, U-Bolts, Equalizers, Radius Rods, are free of damage, excessive wear, Leaks, brackets are attached and seven intact, shocks are properly installed from the seven wear,
		Secure and free of defects. Air bags are intact, shocks are properly installed, free of excessive wear, Leaks, brackets are attached and secure.  Slider Rails are properly.
H	[] []	
	()	Slider Rails are properly secured to the cross members, no gaps or broken welds. Slider Pins are properly Gear straight, braces intact, properly attached to the slider rails.
		Installed and engaged to the slider rails. Slider handle is properly secured. OEM Gussets are intact. Landing and able to be properly secured. OEM Gussets are intact. Landing and able to be properly secured.
		Gear straight, braces intact, properly attached to Wing Plate and Cross Members handle in good condition  All Glad Hand Grommets are five at the condition of the condition of the condition and the condition of
4	0 n	and able to be properly secured attached to Wing Plate and Cross Members is are intact. Landing
	[]	All Glad Hand Grown and Gr
		Panel/bulkheads Aldies are tree of tears and excessive wear. Glad bands
11- 1	1 1	And defects. Air tanks are properly secured by a slider return spring. All airlines are free of wear marks, chaffing
и	[]	Broke mall and drained.
		Manual Ma
		Brake adjustment checked, brake thickness measured, slack adjusters properly secured and operational.  Corrosion. Brake Drums are intact, no excess wear or damage, free of oil and grease.
		The colors well or damage for the color excessive rust and
		Front axle brake thickness RIGHT RIGHT
0 0	1 11	Front axle brake thickness  Rear Axle Brake Thickness  RIGHT  RIGHT  RIGHT
ra [:	1 9	Optional equipment of
		And in good conditional (Lift Gate), batteries secured areas
12 17		Optional equipment is functional (Lift Gate), batteries secured properly. Winches & straps properly secured
ra []	[]	Tires matched 4
		COMMENTS  All lug nuts properly secured, rims are free of cracks, damage, or excessive wear with pool inflated.  All hubs are in good condition with proper field.
		All hubs are in good south. rims are free of cracks, damage or south or belt exposure, properly inflated
TREAD DEP	TH 32/NDS"	Proper fiuld levels.
POSITION	TOPA	Radial = R Radial Posses
LFO	TREAD DE	PTH LBS DOSITION RECEIP = RRC Blas plu - P
LFI		TREAD DEPTH LBS
LRO	10	
LRI		RRO ()
		- RRI
UBOMETE	R	
		Tire Size
SPECTED BY:		RIM TYPE_
	PRINT NAME	Land D.
ICATION. TU	10	SIGNATURE